

ALL STEEL SERVICE

PRODUCT CATALOG



PLATE



SQUARE TUBING



HOT ROLLED SHEETS



RECTANGULAR TUBING



COLD ROLLED SHEETS



FLAT BAR



GALVANIZED SHEETS



ROUNDS



DIAMOND PLATE



SQUARES



WIDE FLANGE BEAMS



ADJUSTABLE COLUMNS



ANGLE



CORRUGATED DECK



BAR CHANNEL



REBAR




STRUCTURAL CHANNEL



BAR GRATING



STRINGER CHANNEL



EXPANDED METAL



PIPE

Note: All Steel Service makes no guarantee regarding the accuracy of the information presented in this catalog. All information should be viewed as rough approximations only. Always consult with a qualified engineer regarding the applicational suitability of metal products.

PLATE

| Thickness (in.) | Width (in.) | Length (in.) | Grade |
|--------------------|----------------|-----------------|--------------|
| 3/16 | 48 | 96 | A36 |
| 3/16 | 48 | 120 | A36 |
| 3/16 | 60 | 120 | A36 |
| 1/4 | 48 | 96 | A36, A572-50 |
| 1/4 | 48 | 120 | A36, A572-50 |
| 1/4 | 60 | 120 | A36, A572-50 |
| 1/4 | 60 | 144 | A36, A572-50 |
| 1/4 | 60 | 240 | A36, A572-50 |
| 1/4 | 96 | 240 | A36, A572-50 |
| 5/16 | 48 | 96 | A36, A572-50 |
| 5/16 | 48 | 120 | A36, A572-50 |
| 5/16 | 60 | 120 | A36, A572-50 |
| 5/16 | 60 | 144 | A36, A572-50 |
| 5/16 | 60 | 240 | A36, A572-50 |
| 5/16 | 72 | 120 | A36, A572-50 |
| 5/16 | 72 | 144 | A36, A572-50 |
| 3/8 | 48 | 96 | A36, A572-50 |
| 3/8 | 48 | 120 | A36, A572-50 |
| 3/8 | 60 | 120 | A36, A572-50 |
| 3/8 | 60 | 144 | A36, A572-50 |
| 3/8 | 60 | 240 | A36, A572-50 |
| 3/8 | 72 | 120 | A36, A572-50 |
| 3/8 | 96 | 240 | A36, A572-50 |
| 1/2 | 48 | 96 | A36, A572-50 |
| 1/2 | 48 | 120 | A36, A572-50 |
| 1/2 | 60 | 120 | A36, A572-50 |
| 1/2 | 72 | 120 | A36, A572-50 |
| 1/2 | 96 | 240 | A36, A572-50 |
| 9/16 | 48 | 120 | A36 |
| 5/8 | 96 | 240 | A36, A572-50 |
| 3/4 | 96 | 240 | A36, A572-50 |
| 7/8 | 96 | 240 | A36, A572-50 |

PLATE

| Thickness (in.) | Width (in.) | Length (in.) | Grade |
|--------------------|----------------|-----------------|--------------|
| 1 | 96 | 240 | A36, A572-50 |
| 1 $\frac{1}{8}$ | 96 | 240 | A36 |
| 1 $\frac{1}{4}$ | 96 | 240 | A36, A572-50 |
| 1 $\frac{3}{8}$ | 96 | 240 | A36 |
| 1 $\frac{1}{2}$ | 96 | 240 | A36, A572-50 |
| 1 $\frac{3}{4}$ | 96 | 240 | A36, A572-50 |
| 2 | 96 | 240 | A36, A572-50 |
| 2 $\frac{1}{4}$ | 96 | 120 | A36, A572-50 |
| 2 $\frac{1}{2}$ | 96 | 120 | A36, A572-50 |
| 2 $\frac{3}{4}$ | 96 | 120 | A36, A572-50 |
| 3 | 96 | 120 | A36, A572-50 |
| 3 $\frac{1}{2}$ | 96 | 120 | A36, A572-50 |

HOT ROLLED SHEETS

| Thickness | Width (in.) | Length (in.) | Grade |
|-----------|----------------|-----------------|-------------|
| 12 ga | 48 | 96 | ASTM A-1011 |
| 12 ga | 48 | 120 | ASTM A-1011 |
| 12 ga | 60 | 120 | ASTM A-1011 |
| 11 ga | 48 | 96 | ASTM A-1011 |
| 11 ga | 48 | 120 | ASTM A-1011 |
| 11 ga | 60 | 120 | ASTM A-1011 |
| 10 ga | 48 | 96 | ASTM A-1011 |
| 10 ga | 48 | 120 | ASTM A-1011 |
| 10 ga | 60 | 120 | ASTM A-1011 |

COLD ROLLED SHEETS

| Thickness | Width (in.) | Length (in.) | Grade |
|-----------|----------------|-----------------|-------------|
| 18 ga | 48 | 120 | ASTM A-1011 |
| 16 ga | 48 | 120 | ASTM A-1011 |
| 14 ga | 48 | 120 | ASTM A-1011 |

GALVANIZED SHEETS

| Thickness | Width (in.) | Length (in.) |
|-----------|----------------|-----------------|
| 18 ga | 48 | 120 |
| 16 ga | 48 | 120 |
| 14 ga | 48 | 120 |

DIAMOND PLATE

| Thickness (in.) | Width (in.) | Length (in.) |
|--------------------|----------------|-----------------|
| 1/8 | 48 | 96 |
| 1/8 | 48 | 120 |
| 3/16 | 48 | 96 |
| 3/16 | 48 | 120 |
| 3/16 | 60 | 144 |
| 1/4 | 48 | 96 |
| 1/4 | 48 | 120 |
| 1/4 | 60 | 120 |
| 3/8 | 48 | 96 |
| 3/8 | 48 | 120 |
| 3/8 | 60 | 120 |
| 1/2 | 48 | 120 |

WIDE FLANGE BEAMS

| Name | Section depth (in.) | Weight/foot (lbs./ft.) | Flange width (in.) | Flange thickness (in.) | Web thickness (in.) |
|----------|---------------------|------------------------|--------------------|------------------------|---------------------|
| W4 x 13 | 4.160 | 13 | 4.060 | .345 | .280 |
| W5 x 16 | 5.010 | 16 | 5.000 | .360 | .240 |
| W5 x 19 | 5.150 | 19 | 5.030 | .430 | .270 |
| W6 x 9 | 5.900 | 9 | 3.940 | .215 | .170 |
| W6 x 12 | 6.030 | 12 | 4.000 | .280 | .230 |
| W6 x 16 | 6.280 | 16 | 4.030 | .405 | .260 |
| W6 x 15 | 5.990 | 15 | 5.990 | .260 | .230 |
| W6 x 20 | 6.200 | 20 | 6.020 | .365 | .260 |
| W6 x 25 | 6.380 | 25 | 6.080 | .455 | .320 |
| W8 x 10 | 7.890 | 10 | 3.940 | .205 | .170 |
| W8 x 13 | 7.990 | 13 | 4.000 | .255 | .230 |
| W8 x 15 | 8.110 | 15 | 4.015 | .315 | .245 |
| W8 x 18 | 8.140 | 18 | 5.250 | .330 | .230 |
| W8 x 21 | 8.280 | 21 | 5.270 | .400 | .250 |
| W8 x 24 | 7.930 | 24 | 6.495 | .400 | .245 |
| W8 x 28 | 8.060 | 28 | 6.535 | .465 | .285 |
| W8 x 31 | 8.000 | 31 | 7.995 | .435 | .285 |
| W8 x 35 | 8.120 | 35 | 8.020 | .495 | .310 |
| W8 x 40 | 8.250 | 40 | 8.070 | .560 | .360 |
| W8 x 48 | 8.500 | 48 | 8.110 | .685 | .400 |
| W10 x 12 | 9.870 | 12 | 3.960 | .210 | .190 |
| W10 x 15 | 9.990 | 15 | 4.000 | .270 | .230 |
| W10 x 17 | 10.110 | 17 | 4.010 | .330 | .240 |
| W10 x 19 | 10.240 | 19 | 4.020 | .395 | .250 |
| W10 x 22 | 10.170 | 22 | 5.750 | .360 | .240 |
| W10 x 26 | 10.330 | 26 | 5.770 | .440 | .260 |
| W10 x 30 | 10.470 | 30 | 5.810 | .510 | .300 |

WIDE FLANGE BEAMS

| Name | Section depth (in.) | Weight/foot (lbs./ft.) | Flange width (in.) | Flange thickness (in.) | Web thickness (in.) |
|----------|---------------------|------------------------|--------------------|------------------------|---------------------|
| W10 x 33 | 9.730 | 33 | 7.960 | .435 | .290 |
| W10 x 39 | 9.920 | 39 | 7.985 | .530 | .315 |
| W10 x 45 | 10.100 | 45 | 8.020 | .620 | .350 |
| W10 x 49 | 9.980 | 49 | 10.000 | .560 | .340 |
| W12 x 14 | 11.910 | 14 | 3.970 | .225 | .200 |
| W12 x 16 | 11.990 | 16 | 3.990 | .265 | .220 |
| W12 x 19 | 12.160 | 19 | 4.005 | .350 | .235 |
| W12 x 22 | 12.310 | 22 | 4.030 | .425 | .260 |
| W12 x 26 | 12.220 | 26 | 6.490 | .380 | .230 |
| W12 x 30 | 12.340 | 30 | 6.520 | .440 | .260 |
| W12 x 35 | 12.500 | 35 | 6.560 | .520 | .300 |
| W12 x 40 | 11.940 | 40 | 8.005 | .515 | .295 |
| W14 x 22 | 13.740 | 22 | 5.000 | .335 | .230 |
| W14 x 26 | 13.910 | 26 | 5.025 | .420 | .255 |
| W14 x 30 | 13.840 | 30 | 6.730 | .385 | .270 |
| W14 x 34 | 13.980 | 34 | 6.745 | .455 | .285 |
| W14 x 38 | 14.100 | 38 | 6.770 | .515 | .310 |
| W16 x 26 | 15.690 | 26 | 5.500 | .345 | .250 |
| W16 x 31 | 15.880 | 31 | 5.525 | .440 | .275 |
| W16 x 36 | 15.860 | 36 | 6.985 | .430 | .295 |
| W16 x 40 | 16.010 | 40 | 6.995 | .505 | .305 |
| W18 x 35 | 17.700 | 35 | 6.000 | .425 | .300 |

ANGLE

| Size (in. x in.) | Thickness (in.) | Weight/foot (lbs./ft.) |
|---------------------|--------------------|---------------------------|
| 3/4 x 3/4 | 1/8 | 0.59 |
| 1 x 1 | 1/8 | 0.80 |
| 1 x 1 | 3/16 | 1.16 |
| 1 x 1 | 1/4 | 1.49 |
| 1 1/4 x 1 1/4 | 1/8 | 1.01 |
| 1 1/4 x 1 1/4 | 3/16 | 1.48 |
| 1 1/4 x 1 1/4 | 1/4 | 1.92 |
| 1 1/2 x 1 1/2 | 1/8 | 1.23 |
| 1 1/2 x 1 1/2 | 3/16 | 1.80 |
| 1 1/2 x 1 1/2 | 1/4 | 2.34 |
| 1 3/4 x 1 3/4 | 1/4 | 2.77 |
| 2 x 1 1/2 | 1/8 | 1.44 |
| 2 x 1 1/2 | 1/4 | 2.77 |
| 2 x 2 | 1/8 | 1.65 |
| 2 x 2 | 3/16 | 2.44 |
| 2 x 2 | 1/4 | 3.19 |
| 2 x 2 | 5/16 | 3.92 |
| 2 x 2 | 3/8 | 4.70 |
| 2 1/2 x 2 | 1/4 | 3.62 |
| 2 1/2 x 2 1/2 | 3/16 | 3.07 |
| 2 1/2 x 2 1/2 | 1/4 | 4.10 |
| 2 1/2 x 2 1/2 | 5/16 | 5.00 |
| 2 1/2 x 2 1/2 | 3/8 | 5.90 |
| 2 1/2 x 2 1/2 | 1/2 | 7.70 |
| 3 x 2 | 1/4 | 4.1 |
| 3 x 2 | 3/8 | 5.9 |
| 3 x 2 | 1/2 | 7.7 |
| 3 x 2 1/2 | 1/4 | 4.5 |
| 3 x 2 1/2 | 5/16 | 5.6 |
| 3 x 2 1/2 | 3/8 | 6.6 |

ANGLE

| Size (in. x in.) | Thickness (in.) | Weight/foot (lbs./ft.) |
|---------------------|--------------------|---------------------------|
| 3 x 3 | 3/16 | 3.7 |
| 3 x 3 | 1/4 | 4.9 |
| 3 x 3 | 5/16 | 6.1 |
| 3 x 3 | 3/8 | 7.2 |
| 3 x 3 | 1/2 | 9.4 |
| 3½ x 2½ | 5/16 | 6.1 |
| 3½ x 3 | 1/4 | 5.4 |
| 3½ x 3 | 5/16 | 6.6 |
| 3½ x 3 | 3/8 | 7.9 |
| 3½ x 3½ | 1/4 | 5.8 |
| 3½ x 3½ | 5/16 | 7.2 |
| 3½ x 3½ | 3/8 | 8.5 |
| 4 x 3 | 1/4 | 5.8 |
| 4 x 3 | 5/16 | 7.2 |
| 4 x 3 | 3/8 | 8.5 |
| 4 x 3 | 1/2 | 11.1 |
| 4 x 3½ | 1/4 | 6.2 |
| 4 x 3½ | 5/16 | 7.7 |
| 4 x 3½ | 3/8 | 9.1 |
| 4 x 3½ | 1/2 | 11.9 |
| 4 x 4 | 1/4 | 6.6 |
| 4 x 4 | 5/16 | 8.2 |
| 4 x 4 | 3/8 | 9.8 |
| 4 x 4 | 1/2 | 12.8 |
| 4 x 4 | 5/8 | 15.7 |
| 4 x 4 | 3/4 | 18.5 |
| 5 x 3 | 1/4 | 6.6 |
| 5 x 3 | 5/16 | 8.2 |
| 5 x 3 | 3/8 | 9.8 |
| 5 x 3 | 1/2 | 12.8 |
| 5 x 3½ | 5/16 | 8.7 |
| 5 x 3½ | 3/8 | 10.4 |
| 5 x 3½ | 1/2 | 13.6 |

ANGLE

| Size (in. x in.) | Thickness (in.) | Weight/foot (lbs./ft.) |
|---------------------|--------------------|---------------------------|
| 5 x 5 | 5/16 | 10.3 |
| 5 x 5 | 3/8 | 12.3 |
| 5 x 5 | 1/2 | 16.2 |
| 5 x 5 | 5/8 | 20.0 |
| 5 x 5 | 3/4 | 23.6 |
| 6 x 3½ | 5/16 | 9.8 |
| 6 x 3½ | 3/8 | 11.7 |
| 6 x 3½ | 1/2 | 15.3 |
| 6 x 4 | 5/16 | 10.3 |
| 6 x 4 | 3/8 | 12.3 |
| 6 x 4 | 1/2 | 16.2 |
| 6 x 4 | 3/4 | 23.6 |
| 6 x 6 | 5/16 | 12.4 |
| 6 x 6 | 3/8 | 14.9 |
| 6 x 6 | 1/2 | 19.6 |
| 6 x 6 | 5/8 | 24.2 |
| 6 x 6 | 3/4 | 28.7 |
| 6 x 6 | 1 | 37.4 |
| 7 x 4 | 3/8 | 13.6 |
| 7 x 4 | 1/2 | 17.9 |
| 7 x 4 | 3/4 | 26.2 |
| 8 x 4 | 1/2 | 19.6 |
| 8 x 4 | 3/4 | 28.7 |
| 8 x 4 | 1 | 37.4 |
| 8 x 6 | 1/2 | 23.0 |
| 8 x 6 | 3/4 | 33.8 |
| 8 x 6 | 1 | 44.2 |
| 8 x 8 | 1/2 | 26.4 |
| 8 x 8 | 3/4 | 38.9 |
| 8 x 8 | 1 | 51.0 |

BAR CHANNEL

| Width (in.) | Height (in.) | Thickness (in.) | Weight/foot (lbs./ft.) |
|----------------|-----------------|--------------------|---------------------------|
| 1 | 1/2 | 1/8 | 0.88 |
| 1½ | 1/2 | 1/8 | 1.12 |
| 2 | 1 | 3/16 | 2.57 |

STRUCTURAL CHANNEL

| Section number | Weight/ foot (lbs./ft.) | Section depth (in.) | Flange width (in.) | Flange thickness (in.) | Web thickness (in.) |
|----------------|-------------------------------|---------------------------|--------------------------|------------------------------|---------------------------|
| C3 | 4.1 | 3 | 1 $\frac{3}{8}$ | 1/4 | 3/16 |
| C3 | 5 | 3 | 1 $\frac{1}{2}$ | 1/4 | 1/4 |
| C4 | 5.4 | 4 | 1 $\frac{5}{8}$ | 5/16 | 3/16 |
| C4 | 7.25 | 4 | 1 $\frac{3}{4}$ | 5/16 | 5/16 |
| C5 | 6.7 | 5 | 1 $\frac{3}{4}$ | 5/16 | 3/16 |
| C5 | 9 | 5 | 1 $\frac{7}{8}$ | 5/16 | 5/16 |
| C6 | 8.2 | 6 | 1 $\frac{7}{8}$ | 5/16 | 3/16 |
| C6 | 10.5 | 6 | 2 | 5/16 | 5/16 |
| C6 | 13 | 6 | 2 $\frac{1}{8}$ | 5/16 | 7/16 |
| C7 | 9.8 | 7 | 2 $\frac{1}{8}$ | 3/8 | 3/16 |
| C8 | 11.5 | 8 | 2 $\frac{1}{4}$ | 3/8 | 1/4 |
| C8 | 13.75 | 8 | 2 $\frac{3}{8}$ | 3/8 | 5/16 |
| C9 | 13.4 | 9 | 2 $\frac{3}{8}$ | 7/16 | 1/4 |
| C10 | 15.3 | 10 | 2 $\frac{5}{8}$ | 7/16 | 1/4 |
| C10 | 20 | 10 | 2 $\frac{3}{4}$ | 7/16 | 3/8 |
| C12 | 20.7 | 12 | 3 | 1/2 | 5/16 |
| C15 | 33.9 | 15 | 3 $\frac{3}{8}$ | 5/8 | 3/8 |

STRINGER CHANNEL

| Section depth | Weight/foot (lbs./ft.) | Flange width (in.) | Web thickness (in.) |
|---------------|------------------------|--------------------|---------------------|
| 10 | 8.4 | 1.50 | .17 |
| 12 | 10.6 | 1.50 | .19 |

PIPE

| Size | I.D. (in.) | O.D. (in.) | Wall thickness (in.) | Weight/foot (lbs./ft.) |
|------|---------------|---------------|----------------------------|---------------------------|
| 1/2 | .622 | .840 | .109 | .85 |
| 3/4 | .824 | 1.050 | .113 | 1.13 |
| 1 | 1.049 | 1.315 | .133 | 1.68 |
| 1¼ | 1.380 | 1.660 | .140 | 2.27 |
| 1½ | 1.610 | 1.900 | .145 | 2.72 |
| 2 | 2.067 | 2.375 | .154 | 3.65 |
| 2½ | 2.469 | 2.875 | .203 | 5.79 |
| 3 | 3.068 | 3.500 | .216 | 7.58 |
| 3½ | 3.548 | 4.000 | .226 | 9.11 |
| 4 | 4.026 | 4.500 | .237 | 10.79 |
| 5 | 5.047 | 5.563 | .258 | 14.62 |
| 6 | 6.065 | 6.625 | .280 | 18.97 |
| 8 | 8.071 | 8.625 | .277 | 24.70 |

SQUARE TUBING

| Side A x Side B (in.) x (in.) | Wall thickness (in.) | Weight/foot (lbs./ft.) |
|----------------------------------|----------------------------|---------------------------|
| 3/4 x 3/4 | 1/8 | 1.028 |
| 1x1 | 1/8 | 1.448 |
| 1¼ x 1¼ | 1/8 | 1.846 |
| 1½ x 1½ | 1/8 | 2.252 |
| 1½ x 1½ | 3/16 | 3.350 |
| 1½ x 1½ | 1/4 | 4.070 |
| 2 x 2 | 1/8 | 3.070 |
| 2 x 2 | 3/16 | 4.32 |
| 2 x 2 | 1/4 | 5.41 |
| 2½ x 2½ | 1/8 | 3.910 |
| 2½ x 2½ | 3/16 | 5.61 |
| 2½ x 2½ | 1/4 | 7.11 |
| 3 x 3 | 1/8 | 4.652 |
| 3 x 3 | 3/16 | 6.89 |
| 3 x 3 | 1/4 | 8.81 |
| 3 x 3 | 3/8 | 12.16 |
| 4 x 4 | 1/8 | 4.760 |
| 4 x 4 | 3/16 | 9.45 |
| 4 x 4 | 1/4 | 12.21 |
| 4 x 4 | 5/16 | 14.83 |
| 4 x 4 | 3/8 | 17.27 |
| 4 x 4 | 1/2 | 21.63 |
| 5 x 5 | 1/4 | 15.62 |
| 5 x 5 | 5/16 | 19.08 |
| 5 x 5 | 3/8 | 22.37 |
| 5 x 5 | 1/2 | 28.43 |
| 6 x 6 | 1/4 | 19.02 |
| 6 x 6 | 5/16 | 23.34 |
| 6 x 6 | 3/8 | 27.48 |
| 6 x 6 | 1/2 | 35.24 |

RECTANGULAR TUBING

| Side A x Side B (in.) x (in.) | Wall thickness (in.) | Weight/foot (lbs./ft.) |
|----------------------------------|----------------------------|---------------------------|
| 2 x 1 | 1/8 | 2.252 |
| 3 x 2 | 1/8 | 3.91 |
| 3 x 2 | 3/16 | 5.61 |
| 3 x 2 | 1/4 | 7.11 |
| 4 x 2 | 1/8 | 4.75 |
| 4 x 2 | 3/16 | 6.89 |
| 4 x 2 | 1/4 | 8.81 |
| 6 x 2 | 1/8 | 6.46 |
| 6 x 2 | 1/4 | 12.21 |
| 6 x 3 | 1/4 | 13.91 |
| 6 x 4 | 1/4 | 15.62 |
| 6 x 4 | 3/8 | 22.37 |

FLAT BAR

| Thickness (in.) | Width (in.) | Weight/foot (lbs./ft.) |
|--------------------|----------------|---------------------------|
| 1/4 | 1 | .85 |
| 1/4 | 1½ | 1.28 |
| 1/4 | 2 | 1.70 |
| 1/4 | 2½ | 2.13 |
| 1/4 | 3 | 2.55 |
| 1/4 | 3½ | 2.98 |
| 1/4 | 4 | 3.40 |
| 1/4 | 4½ | 3.83 |
| 1/4 | 5 | 4.25 |
| 1/4 | 6 | 5.10 |
| 1/4 | 7 | 5.95 |
| 1/4 | 8 | 6.80 |
| 1/4 | 10 | 8.51 |
| 1/4 | 12 | 10.21 |
| 3/8 | 1 | 1.28 |
| 3/8 | 1½ | 1.91 |
| 3/8 | 2 | 2.55 |
| 3/8 | 2½ | 3.19 |
| 3/8 | 3 | 3.83 |
| 3/8 | 3½ | 4.46 |
| 3/8 | 4 | 5.10 |
| 3/8 | 4½ | 5.74 |
| 3/8 | 5 | 6.38 |
| 3/8 | 6 | 7.65 |
| 3/8 | 7 | 8.93 |
| 3/8 | 8 | 10.20 |
| 3/8 | 9 | 11.49 |
| 3/8 | 10 | 12.76 |
| 3/8 | 12 | 15.31 |

FLAT BAR

| Thickness (in.) | Width (in.) | Weight/foot (lbs./ft.) |
|--------------------|----------------|---------------------------|
| 1/2 | 1 | 1.70 |
| 1/2 | 1½ | 2.55 |
| 1/2 | 2 | 3.40 |
| 1/2 | 2½ | 4.25 |
| 1/2 | 3 | 5.10 |
| 1/2 | 3½ | 5.95 |
| 1/2 | 4 | 6.80 |
| 1/2 | 4½ | 7.65 |
| 1/2 | 5 | 8.50 |
| 1/2 | 6 | 10.20 |
| 1/2 | 7 | 11.90 |
| 1/2 | 8 | 13.60 |
| 1/2 | 9 | 15.31 |
| 1/2 | 10 | 17.02 |
| 1/2 | 12 | 20.42 |
| 3/4 | 2 | 5.10 |
| 3/4 | 3 | 7.65 |
| 3/4 | 4 | 10.20 |
| 3/4 | 5 | 12.75 |
| 3/4 | 6 | 15.30 |
| 3/4 | 8 | 20.40 |
| 3/4 | 12 | 30.63 |
| 1 | 2 | 6.80 |
| 1 | 3 | 10.20 |
| 1 | 4 | 13.60 |
| 1 | 5 | 17.00 |
| 1 | 6 | 20.40 |
| 1 | 7 | 23.80 |
| 1 | 8 | 27.20 |

ROUNDS

| Diameter (in.) | Weight/ foot (lbs./ft.) |
|-------------------|-------------------------------|
| 1/4 | .1669 |
| 3/8 | .3755 |
| 1/2 | .6676 |
| 5/8 | 1.0431 |
| 3/4 | 1.5021 |
| 1 | 2.6704 |
| 1¼ | 4.1724 |
| 1½ | 6.0083 |
| 2 | 10.6814 |

SQUARES

| Size (in.) | Weight/ foot (lbs./ft.) |
|---------------|-------------------------------|
| 1/2 | .850 |
| 5/8 | 1.33 |
| 3/4 | 1.91 |
| 1 | 3.40 |

ADJUSTABLE COLUMNS

| O.D. (inches) | Wall thickness | Range of adjustment |
|------------------|-------------------|------------------------|
| 3½ | 11 ga | 7'-0" – 7'-4" |
| 3½ | 11 ga | 7'-3" – 7'-7" |
| 3½ | 11 ga | 8'-3" – 8'-7" |
| 4 | 11 ga | 7'-0" – 7'-4" |
| 4 | 11 ga | 7'-2" – 7'-6" |
| 4 | 11 ga | 7'-3" – 7'-7" |
| 4 | 11 ga | 7'-11" – 8'-3" |
| 4 | 11 ga | 8'-1" – 8'-5" |
| 4 | 11 ga | 8'-3" – 8'-7" |
| 4 | 11 ga | 10'-3" – 10'-7" |

CORRUGATED DECK

Coming soon!

REBAR

Coming soon!

BAR GRATING

Coming soon!

EXPANDED METAL

| Description | Short way of diamond [SWD] opening (inches) | Long way of diamond [LWD] opening (inches) | Width (inches) | Length (inches) |
|-------------|---|--|-------------------|--------------------|
| 3/4" #9 | .923 | 2.100 | 48 | 96 |
| 1/2", #13 | .500 | 1.260 | 48 | 96 |
| 1/2", #16 | .480 | 1.260 | 48 | 96 |

* Expanded metal products are made from carbon steel and are hot-rolled. They are flattened (i.e not raised or serrated) and come with a regular mill finish (i.e. not primed or galvanized).

† The Long Way of Diamond (LWD) opening runs parallel to the length of the sheet.